



High Current DC Power Supply 40V 1125A 1500A to 3000A 4875A

Model (40V)	Rated Output				Cabinet size WxHxD (mm)	Net weight
	V	A	W	OVP		
PCL40-1125	40V	1125A	45kW	0~42V	600x734.6x732 (12U)	110kg
PCL40-1500	40V	1500A	60kW	0~42V	600x734.6x732 (12U)	140kg
PCL40-1875	40V	1875A	75kW	0~42V	600x1161x732 (20U)	190kg
PCL40-2250	40V	2250A	90kW	0~42V	600x1161x732 (20U)	220kg
PCL40-2625	40V	2625A	105kW	0~42V	600x1560.7x732 (30U)	290kg
PCL40-3000	40V	3000A	120kW	0~42V	600x1560.7x732 (30U)	320kg
PCL40-3375	40V	3375A	135kW	0~42V	600x1560.7x732 (30U)	350kg
PCL40-3750	40V	3750A	150kW	0~42V	600x1560.7x732 (30U)	380kg
Voltage ripple	≤0.5%FS+100mV (20Hz to 1MHz)					
AC input	3φ4W (L1, L2, L3, PE), 380V±10% 47~63Hz (at default) 3φ4W (L1, L2, L3, PE), 440V/480V±10% 47~63Hz (at request)					